



Thank you for purchasing the Deflector Brake! Please follow the application directions pictured below to achieve the best results. The Deflector Brake was designed for the standard M4 M16 AR15 style upper so please only use these models (seen below). Apply the Deflector Brake at least 24 hours prior to when you plan on shooting. Apply in temperatures above 60 Degrees Fahrenheit and prior to application ensure your brass deflector is clean and dry (free from oil or lubricant). Note: The shelf life of the adhesive is 2 years.



Step 1: Remove the adhesive backing. Try not to touch the adhesive.



Step 2: Line the Deflector Brake up on the brass deflector as far forward as possible while ensuring the dust cover operates.



Step 3: It is really important to push down all over the part to activate the adhesive (it is pressure sensitive). Do this for at least 10 seconds, let it sit for 5-10 min and repeat this 2 more times. Push down on it prior to shooting as well. Once the part is secure it will likely stay on until you pull it off. We recommend changing the part after every 300 rounds. The part will not continue to work as well much past that. Your pattern of deflection will start to creep/grow and the part itself will be physically degraded.

Thank you again for purchasing the Deflector Brake. We hope brass burns become a thing of the past. You save some extra brass for re-loading, your rifle stays newer looking and your brass cleanup is no time flat!



For more information about the Deflector Brake contact Donnie@havoctactical.com